

Bradnam's
sliding doors

The ultimate view...



Pradella Group



essential range

Key Features and Benefits

- Stylish handle is fitted with mortice lock for superior security
- Conveniently located key cylinders for easier operation
- Precision Euro track roller system for effortless, smooth sliding action
- Rounded and capped sections protect curtains from sharp edges
- Insect and security screen options easily installed within the frame
- Easy cleaning – most vacuum heads fit easily within the wide door track

Performance Parameters

Frame sizes	80mm / 140mm
Maximum door height	2450mm
Maximum door width	6246mm
Maximum panel width	1350mm
Maximum panel weight	50kg
Maximum water rating	300pa
Maximum wind rating	3300Pa ULS
Maximum glass thickness	6.76mm
Maximum acoustic rating	Rw30
Maximum bushfire rating	BAL 40

Note: Features, benefits and performance parameters are subject to local variations, climate requirements and confirmation of structural performance

Endless possibilities across the range...



signature range

Key Features and Benefits

- Innovative corner and cavity configurations for a luxury indoor/outdoor lifestyle
- Stylish handle is fitted with mortice lock for superior security
- Conveniently located key cylinders for easy operation
- Precision Euro track roller system for effortless, smooth sliding action
- Rounded and capped sections protect curtains from sharp edges
- Insect and security screen options easily installed within the frame
- Easy cleaning – most vacuum heads fit easily within the wide door track

Performance Parameters

Frame sizes	100mm / 166mm
Maximum door height	2700mm
Maximum door width	6246mm
Maximum panel width	1350mm
Maximum panel weight	100kg
Maximum water rating	600pa*
Maximum wind rating	4500Pa ULS
Maximum glass thickness	12.76mm (single glazed) 20mm (IGUs)
Maximum acoustic rating	Rw44
Maximum bushfire rating	BAL 40

** Does not apply to 166mm frame*

The performance figures above do not apply to cavity configurations



commercial range

Key Features and Benefits

- Innovative corner and cavity configurations for a luxury indoor/outdoor lifestyle
- Stylish handle is fitted with mortice lock for superior security
- Conveniently located key cylinders for easy operation
- Precision Euro track roller system for effortless, smooth sliding action
- Rounded and capped sections protect curtains from sharp edges
- Insect and security screen options easily installed within the frame
- Easy cleaning – most vacuum heads fit easily within the wide door track

Performance Parameters

Frame sizes	100mm / 150mm 200mm / 250mm
Maximum door height	3100mm
Maximum door width	12000mm
Maximum panel width	1800mm
Maximum panel weight	160kg
Maximum water rating	650pa
Maximum wind rating	6000Pa ULS
Maximum glass thickness	10.76mm (single glazed) 28mm (IGUs)
Maximum acoustic rating	Rw34
Maximum bushfire rating	BAL 40

The performance figures above do not apply to cavity configurations

Say goodbye to convention...



cavity sliding doors

signature | commercial

A fusion of ingenuity and practicality

Bradnam's **Cavity Sliding Doors** will revolutionise how outdoor and entertainment areas are designed. Unlike traditional 'entertainment doors' such as stacker doors or bi-fold doors, our Cavity Doors truly provide unobstructed views and access. Seamlessly gliding out of sight, they don't have fixed or folded panels blocking the view or access from the inside to the outside.



Turn a tight corner
into the ultimate view...

Spectacular from any angle

Be it a new architecturally designed home or a renovation enhancement of an existing property, our **Corner Sliding Doors** are perfect for joining living areas with gardens, patios or pool areas. They are capable of spanning either a 90 or 135 degree angle without a post, providing better access and view compared to standard sliding or stacker doors.

windows | doors | balustrade | insect & safety screens | showerscreens | mirrors & wardrobes



Australian
Owned & Made

Bradnam's products are proudly made
in Australia and designed specifically
to meet all Australian conditions



Note: Products may be subject to local variation, regulatory requirements and confirmation of structural performance. Screening not available in selected configurations.